

Power Distribution Unit - Expert PDU basic 8110/8111

8 x     



Expert PDU basic 8110
Power Ports on the rear panel



Expert PDU basic 8111
Power Ports on the front panel

Electrical Connections

- 1 Power Input (IEC C20,max. 16A)
- 8 Power Ports (IEC C13, max. 10A)
- Ethernet connector RJ45 (10/100 MBit)
- 2 mini-DIN connectors for optional sensors or serial interface

Technical Details

- 19 inch, 1 RU
- Weight: 2,2 kg
- Operating temperature: 0-50 °C (non-condensing)

Features

- Clearly visible LED display for total current (actual,max), IP address, sensor data and error reports
- Metered Power Distribution Unit to distribute power and meter the total current (no power switching function)
- Firmware update via Ethernet during operation
- HTTP 1.1, DHCP, SNMPv1 (traps), SNMPv2c (traps), Syslog
- Access control via IP Access Control List
- Access control via optional HTTP password
- Low power consumption: max. 3 Watt

Ordering Information

Article Number	Product	Description	Operating Voltage	Maximum Current	EAN Code
8110	Expert PDU basic 8110	Power connectors on the rear panel	230V	16A	4250493181106
8111	Expert PDU basic 8111	Power connectors on the front panel	230V	16A	4250493181113
7001	Temperature sensor	-20°C to +80°C			4250493170018
7002	Hybrid sensor	-20°C to +80°C / 0-100% humidity			4250493170025
7990	Serial connector cable				4250493179905